



## ◆ Specifications /規格表:

Model 型號	FZ-KP2	FZ-KP2I	FZ-KP2T
	FZ-KP2K	FZ-KP2IK	FZ-KP2TK
Emitting light 發光源	Red LED (625nm)	IR LED (940nm)	Red LED (625nm)
Operating voltage 工作電壓	12 to 24 VDC 10%		
Current consumption 消耗電流	35mA max		40mA max
Output current 輸出電流	100mA max(24VDC max.), Residual voltage :1V max		
Output type 輸出模式	NPN and PNP L-on / D-on		
Protection circuit 保護電路	Reversed polarity protection, over-current protection, surge absorber		
Response time 反應時間	0.5 msec		1 msec
Indicators 指示燈	Output indicator : Red LED, Power indicator : Green LED		
Sensitivity adjustment 靈敏度功能	4-turns trimmer		
Timer function 計時器功能			One shot 0~7 sec off-delay (switch selectable)
Material 外觀材質	ABS Resin		
Wiring method / 出線方式	FZ-□ KP2	Pre-wired Ø4.2 M / 4-cores	
	FZ-□ KP2K	M12 Pigtailed type M12接頭 15cm電線式	
Weight 重量	FZ-□ KP2	Approx. 85 g	
	FZ-□ KP2K	Approx. 55 g	

## ◆ Dimensions /外型尺寸圖:

