

◆Shape/外觀：



◆Specifications / 規格表：

Model / 型號	RMF-10KP2	RMF-10KP2K	RMF-DU30KP2	RMF-DU30KP2K
Sensing type / 檢出方式	Through beam / 對照式		Diffuse reflection / 擴散反射式	
Sensing distance / 檢出距離	10M		30 cm	
Emitting light / 發光源	Infrared LED 850 nm		Infrared LED 875 nm	
Operating voltage / 工作電壓	DC12 ~ 24 V			
Current Consumption / 消耗電流	45 mA Max./Each side		30 mA Max.	
Load current / 負載電流	100mA Max. at DC24V			
Output type / 輸出模式	NPN N.O./N.C.		PNP N.O./N.C.	
Response time / 反應時間	1.5 ms Max.			
Insulation resistance / 隔離阻抗	20MΩ min. (DC500V)			
Voltage withstandability / 絕緣耐壓	AC1000V 60Hz for 60 Sec.			
Operating temperature / 工作溫度	- 25 °C ~ + 60 °C			
Ambient humidity / 工作溼度	35% ~ 85% RH			
Protection degree / 防水等級	IP66			
Material / 外觀材質	ABS			
Wiring method / 出線方式	Pre-wired Ø5.2 x 2 M / 4-wires	M12 pigtailed type / M12 接頭15cm電線式	Pre-wired Ø4.2 x 2M / 4-wires	M12 pigtailed type / M12 接頭15cm電線式
Weight / 重量	Approx.160g	Approx.60g	Approx.80g	Approx.40g

◆Dimensions/尺寸圖：

