

◆Shape/外觀：



◆Specifications / 規格表：

Model / 型號	RMF-10 □ RMF-20 □	RMF-10 □ K RMF-20 □ K	RMF-10 □ K1 RMF-20 □ K1
Sensing type / 檢出方式	Through beam / 對照式		
Sensing distance / 檢出距離	10 M 20 M		
Emitting light / 發光源	Infrared LED 850 nm		
Operating voltage / 工作電壓	DC12 ~ 24 V		
Current Consumption / 消耗電流	45 mA Max.		
Load current / 負載電流	200mA Max. at DC24V		
Output type / 輸出模式	□N : NPN L.on/D.on / □P : PNP L.on/D.on		
Response time / 反應時間	1.5 ms Max.		
Insulation resistance / 隔離阻抗	20MΩ min. (DC500V)		
Voltage withstandability / 絕緣耐壓	AC1000V 60Hz for 60 Sec.		
Operating temperature/工作溫度	- 20 °C ~ + 55°C		
Ambient humidity / 工作溼度	35% ~ 85% RH		
Protection degree / 防水等級	IP66		
Material / 外觀材質	ABS		
Wiring method / 出線方式	RX:Pre-wired / 4-wire Ø5.2 x 2 M TX:Pre-wired / 2-wire Ø5.2 x 2 M	M12 pigtailed connector type / M12 接頭15cm電線式	M12 plug-in connector type / M12 接頭
Weight / 重量	Approx.165g	Approx.70g	Approx.40g

◆Dimensions/尺寸圖：

