◆Characteristics / 特點：

- Suitable for the detection of tiny metal passing.
  / 適合檢測通過的微小金屬
- The pigtailed type connector makes its replacement easy.
  / 有端子式，讓您能夠迅速的更換
- 12-turn Sensitivity Adjuster. Users can adjust the sensitivity more optimum according to different objects.
  /可調式旋鈕(12轉)，可依據感測物的大小而有所調整
- Dual LED makes you easy to know the current operating situation.
  / 後端雙LED顯示，能夠讓您在使用時容易判斷輸出的狀況

◆Specifications / 規格表：

Model / 型號	Pre-wired Ø4.2	SIR15-KP2	SIR22-KP2	SIR30-KP2
	M12 Pigtailed type	SIR15-KP2K1	SIR22-KP2K1	SIR30-KP2K1
Sensing hole diameter / 檢測孔直徑		D=15mm	D=22mm	D=30mm
Min. detecting object / 最小檢測物		2mm min.	3mm min.	3mm min.
Operating voltage / 工作電壓		DC 12 ~ 24V		
Current consumption / 消耗電流		15 mA		
Load current / 負載電流		100 mA Max at DC 24V		
Output method / 輸出模式		NPN N.O./N.C. PNP NO./NC.		
Operating temperature / 工作溫度範圍		-20℃ ~ + 60℃		
Protection degree / 防水等級		IP 66		
Wiring method / 出線方式	SIR-□KP2	Ø4.2 x 2M / 4-wires		
	SIR-□KP2K1	M12 Pigtailed type/ M12接頭 15cm電線式		
Weight / 重量	SIR-□KP2	Approx.86g	Approx.85g	Approx.81g
	SIR-□KP2K1	Approx.30g	Approx.29g	Approx.25g

◆Dimensions/尺寸圖：

SIR□-KP2



SIR□-KP2K1